



# MATERIAL SAFETY DATA SHEET

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: **AUTOSEAL 3462B**  
Product Use/Class: **AQUEOUS COATING, PART B**

**LORD CORPORATION**  
**111 LORD DRIVE**  
**CARY, NC 27511-7923**

**TRANSPORTATION EMERGENCY:**  
**CHEMTREC 24 HR EMERGENCY NO.**  
**800 424-9300**  
**(Outside Continental U.S. 703 527-3887)**

**INFORMATION TELEPHONE:**  
**814 868-0924**

**NON-TRANSPORTATION EMERGENCY:**  
**814 763-2345**

EFFECTIVE DATE: 12/03/2010

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Weight % Less Than</u>	<u>ACGIH TLV- TWA</u>	<u>ACGIH TLV- STEL</u>	<u>OSHA PEL- TWA</u>	<u>OSHA PEL- CEILING</u>	<u>Skin</u>
1-Methoxy-2-propyl acetate	108-65-6	50.0 %	N.E.	N.E.	N.E.	N.E.	N.A.
Sodium dioctyl sulfosuccinate	577-11-7	5.0 %	N.E.	N.E.	N.E.	N.E.	N.A.
Dipropylene glycol dimethyl ether	111109-77-4	5.0 %	N.E.	N.E.	N.E.	N.E.	N.A.

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

## 3. HAZARDS IDENTIFICATION

**\*\*\* EMERGENCY OVERVIEW \*\*\*:** Gold Liquid, with Solvent odor. Combustible liquid and vapor. Vapor harmful; may affect the brain or nervous system causing dizziness, headache or nausea. Causes eye irritation. May cause respiratory tract irritation. May cause skin irritation. This product contains a residual amount of a chemical substance that may cause an allergic skin and/or respiratory reaction.

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** May cause severe eye irritation.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** May cause skin irritation.

**EFFECTS OF OVEREXPOSURE - INHALATION:** Possible irritation of the respiratory system can occur causing a variety of symptoms such as dryness of the throat, tightness of the chest, and shortness of breath. May cause central nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Repeated or prolonged solvent overexposure may result in permanent central nervous system damage. Prolonged or repeated contact may result in dermatitis.

**PRIMARY ROUTE(S) OF ENTRY:** Skin Contact, Inhalation, Ingestion, Eye Contact

## 4. FIRST AID MEASURES

**FIRST AID - EYE CONTACT:** Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

30000002901

**FIRST AID - SKIN CONTACT:** Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

**FIRST AID - INHALATION:** Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

**FIRST AID - INGESTION:** If swallowed, do not induce vomiting. Give victim one or two glasses of water or milk. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

## 5. FIRE-FIGHTING MEASURES

**FLASH POINT:** 108 °F, 42 °C  
Setaflash Closed Cup

**LOWER EXPLOSIVE LIMIT (%):** 1.3 %(V)  
**UPPER EXPLOSIVE LIMIT (%):** 13.1 %(V)

**AUTOIGNITION TEMPERATURE:** N.D.

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Combustible liquid and vapor. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, open flame, and other sources of ignition. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool.

**SPECIAL FIREFIGHTING PROCEDURES:** Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water spray may be ineffective. If water is used, fog nozzles are preferable.

## 6. ACCIDENTAL RELEASE MEASURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Keep non-essential personnel a safe distance away from the spill area. Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid breathing vapors. Use self-contained breathing equipment. Notify appropriate authorities if necessary. Contain and remove with inert absorbent material and non-sparking tools. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the MSDS form.

## 7. HANDLING AND STORAGE

**HANDLING:** Keep closure tight and container upright to prevent leakage. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation. Because empty containers may retain product residue and flammable vapors, keep away from heat, sparks and flame; do not cut, puncture or weld on or near the empty container. Do not smoke where this product is used or stored.

**STORAGE:** Do not store or use near heat, sparks, or open flame. Refer to OSHA 29CFR Part 1910.106 "Flammable and Combustible Liquids" for specific storage requirements. Store only in well-ventilated areas. Do not puncture, drag, or slide container. Keep container closed when not in use.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits. Caution: Solvent vapors are heavier than air and collect in lower levels of the work area.

**RESPIRATORY PROTECTION:** Use a NIOSH approved chemical/mechanical filter respirator designed to remove a combination of particulates and organic vapor if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. Observe OSHA regulations (29CFR 1910.134) for respirator use.

**SKIN PROTECTION:** Use neoprene, nitrile, or rubber gloves to prevent skin contact.

**EYE PROTECTION:** Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

**OTHER PROTECTIVE EQUIPMENT:** Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

**HYGIENIC PRACTICES:** Wash hands before eating, smoking, or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>ODOR:</b>	Solvent	<b>BOILING RANGE:</b>	38 - 146 °C
<b>APPEARANCE:</b>	Gold	<b>VAPOR PRESSURE:</b>	N.D.
<b>PHYSICAL STATE:</b>	Liquid	<b>VAPOR DENSITY:</b>	Heavier than Air
<b>ODOR THRESHOLD:</b>	N.D.	<b>EVAPORATION RATE:</b>	Not Applicable
<b>SOLUBILITY IN H2O:</b>	Soluble	<b>DENSITY, LB/GL:</b>	8.67 lb/gal
<b>pH:</b>	6.0	<b>VOLATILE BY WEIGHT:</b>	48.75 %
<b>FREEZE POINT:</b>	N.D.	<b>VOLATILE BY VOLUME:</b>	51.52 %
<b>COEFFICIENT OF WATER/OIL DISTRIBUTION:</b>	N.D.		

(See section 16 for abbreviation legend)

## 10. STABILITY AND REACTIVITY

**CONDITIONS TO AVOID:** High temperatures. Sources of ignition.

**INCOMPATIBILITY:** Strong acids, bases, and strong oxidizers.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of nitrogen., Carbon monoxide, carbon dioxide., Oxides of sulfur.

**HAZARDOUS POLYMERIZATION:** Hazardous polymerization will not occur under normal conditions.

**STABILITY:** Product is stable under normal storage conditions.

## 11. TOXICOLOGICAL INFORMATION

<b>PRODUCT LD50</b>	<b>(ORAL)</b>	No Data
	<b>(DERMAL)</b>	No Data
<b>PRODUCT LC50</b>		No Data

## 12. ECOLOGICAL INFORMATION

**ECOLOGICAL INFORMATION:** No Information

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

## 14. TRANSPORT INFORMATION

**DOT PROPER SHIPPING NAME:** Adhesives  
**DOT HAZARD CLASS:** 3  
**SECONDARY HAZARD:** None  
**DOT UN/NA NUMBER:** 1133  
**PACKING GROUP:** III  
**EMERGENCY RESPONSE GUIDE NUMBER:** 128

The listed transportation classification applies to US DOT non-bulk road shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance department.

## 15. REGULATORY INFORMATION

### U.S. FEDERAL REGULATIONS: AS FOLLOWS -

This product is considered hazardous as defined by 29 CFR 1910.1200 (OSHA HazCom Standard.)

### SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.

:

NONE

### TOXIC SUBSTANCES CONTROL ACT:

### INVENTORY STATUS

The chemical substances in this product are on the TSCA Section 8 Inventory.

### EXPORT NOTIFICATION

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u>	<u>CAS Number</u>
Dipropylene glycol dimethyl ether	111109-77-4

## 16. OTHER INFORMATION

**HMIS RATINGS - HEALTH:** 2\*    **FLAMMABILITY:** 2    **PHYSICAL HAZARD:** 0

\* - Indicates a chronic hazard; see Section 3

### VOLATILE ORGANIC COMPOUNDS

Calculated: 4.16 lb/gal, 498 g/l

**LEGEND:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

## DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred

by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.